



## Engineering Data Sheet : 19101, 19102, 19104

### Unit Information

Model #: 19101, 19102, 19104  
 UPC-IC : 1673119101 / 02 / 04

### Master Pack Dimensions

Weight: 7 lbs. 10 oz (3.46 kg)  
 Cube: 1.03 ft<sup>3</sup> (.03 m<sup>3</sup>)  
 Cube Dimensions: 15.875" x 6.375" x 10.5"  
 Quantity: 12 pcs.

### Specifications

Power Source: 3 C Cell  
 Bulb/Lamp: XPR3  
 Bulb/Lamp Life: 30 Hours  
 Light Output: 50,000 Beam Candlepower  
 Weight (W/o batteries): 6.34 oz (.18 kg)  
 Weight (w/ batteries) 16.3 oz (.46 kg)  
 Replacement Bulb: XPR3 #21300  
 Burn Time (continuous) 5 hours

### Components

Lens Ring: Super-Tough Nylon w/ TPE  
 Lens: Polycarbonate  
 Reflector: Ultem 1000  
 Tube: Super-Tough Nylon  
 Contact Strip: Spring Steel  
 Belt Clip: Super Tough Nylon  
 Lanyard: Braided Nylon (Black)

### Product Features

- Submersible to 100ft
- Non Conductive
- Limited Lifetime Warranty
- Passes 30 feet drop onto concrete
- Waterproof
- Pushbutton Switch
- Pre-focused spot beam
- 50,000 Candlepower, 5 hr continuous w/ alkaline batteries
- Key Ring, Lanyard, and Belt Clip Standard
- Self venting
- Can be converted to a Rechargeable

### Unit Dimensions

Length: 8.63 in. (21.92 cm)  
 Width: 2.33 in. (5.91 cm) at head  
 Height: N/A

### Safety Approvals

**UL:** Class I, Div 1, Group D / Class I, Div 2, Group A, B, C & D  
 Class II, Div 2, Group G  
 Operating Temp T3A  
**CSA:** Class I, Div 2, Group A,B,C & D / Class II, Div 2, Group G  
 Operating Temp Code: T3  
**MSHA** Approved



### Accessories

<u>Accessories</u>	<u>Description</u>
500299	Charger Base
500202-N	Ni-Cad Battery Pack
20641	120V AC Adapter
500180	12-24V DC Adapter
23853	6 ½" Red Snap In Wand
23860	6 ½" Yellow Snap In Wand

### Part #'s:

<u>Part #'s:</u>	<u>Description</u>
19101	Orange Alkaline
19102	Yellow Alkaline
19104	Black Alkaline