

www.flashlight.com

Engineering Data Sheet : 200201

Unit Information

UPC-IC: 16731 200201 (Orange)
 16731 200202 (Yellow)
 16731 200203 (Black)

Unit Dimensions

Length: 6.7ö
 Width: 2.34ö
 Height: N/A

Master Pack Dimensions

Weight: 5 lbs. .4 oz.
 Cube: 1.03 ft³ (.03 m³)
 Cube Dimensions: 15.875ö x 6.375ö x 10.5ö
 Quantity: 12 pcs.

Specifications

Power Source: 2 C Cell
 Bulb/Lamp: Xenon
 Bulb/Lamp Life: 15 Hours
 Light Output: 30,000 Beam Candlepower
 Weight (Without batteries): 6.7 oz.
 Replacement Bulb: XPR2C
 Approximate Burn time during continuous use: 5 hours 40 min.
 Approximate Burn time during intermittent use: 6 hours 30 min.

Components

Contact Strip: Brass
 Lanyard: Braided Nylon (Black)
 Belt Clip: Super-Tough Nylon
 Switch Boot: Thermoplastic Elastomer (TPE)
 Tube: Super-Tough Nylon
 Lens: Polycarbonate with Thermoplastic Elastomer (TPE)
 Reflector: Ultem 1000

Product Features

- UL Division 1 & 2 Listed
- Non-Conductive
- Passes 30 foot drop onto concrete
- 30,000 Candlepower
- Pushbutton Switch
- Pre-focused spot beam

Safety Approvals:

UL: Class I, Div 1, Group D / Class I, Div 2 Group A, B, C & D
 Class II, Div 2, Group G
 Operating Temp T3A
 CSA: Class I, Div 2 Group A, B, C & D / Class II, Div 2 Group G
 Operating Temp T3A
 MSHA: Approved
 When used with a KPR102, KPR104 or PR2
Bulb:
 Class I, Div 1, Group C & D
 Operating Temp T3C
 ATEX II 2 G EEX ib e IIB T3



<u>Part #s</u>	<u>Description:</u>
200201	Orange
200202	Yellow
200203	Black

- Key-Ring Lanyard & Belt Clip Standard
- Lifetime Warranty
- Xenon Bulb
- Submersible 100ft