



Engineering Data Sheet: 2117

Unit Information

Model #: 2117 / Item # 13740
 UPC-IC (12 Digit): 01673137403

Master Pack Dimensions

Weight: 4.9 lbs. (2.2 kg)
 Cube: 0.39 ft³ (0.01 m³)
 Quantity: 12

Specifications

Power Source: 2xD-cell
 Alkaline or Carbon Zinc
 Bulb/Lamp: PR-2
 Bulb/Lamp Life: 15 Hours
 Light Output: 10,000 Beam
 Candlepower
 Weight (Without batteries):
 4.5 oz (.13 kg)

Components

Lens Ring: Polypropylene
 (Black)
 Lens: Unbreakable Tuflexx®
 Reflector: ABS
 Tube: Polypropylene (Safety
 Orange)
 Contact Strip: Phosphor
 Bronze
 Switch: Polyethylene
 Bottom Cap: Polypropylene
 (Black)
 Ring Hanger: ABS (Safety
 Orange)

Product Features

- For use in hazardous atmospheres
- Division 1 UL & CUL approved
- Lower cost of maintenance
- Spare bulb compartment
- Crush Resistant Case
- Switch Guard

Unit Dimensions

Length: 8.1 in. (20.6 cm)
 Width: 2.3 in. (5.8 cm) at head
 Height: N/A

Safety Approvals

UL/CUL: Class I, Div 1, Group C & D
 Div 2, Group A, B, C, & D
 Class II, Div 1, Group G
 Class III
 Operating Temp T3C
CSA: Class I, Group C & D
 Class II, Group G
 Operating Temp T3C
ASTM & MSHA Approved



Worksafe Model # 2117

Accessories

23853
 23860

Description

6 1/2" Red Snap In Wand
 6 1/2" Yellow Snap In Wand

- Ring Hanger
- 250,000 cycle positive locking switch
- Anti-roll tube
- Oversized, faceted reflector for more light
- Unbreakable Lens