



Engineering Data Sheet : 2124

Unit Information

Model #: 2124 / Item # 14240
 UPC-IC (12 Digit): 01673142407

Master Pack Dimensions

Weight: 5.1 lbs.
 Cube: 0.48 ft³
 Quantity: 12

Specifications

Power Source: Carbon Zinc Only: 3xD-cell
 Bulb/Lamp: PR-3
 Bulb/Lamp Life: 15 Hours
 Light Output: 15,000 Beam Candlepower
 Weight (Without batteries): 6.0 oz (.17 kg)

Components

Lens Ring: Polypropylene (Black)
 Lens: Unbreakable Tuflexx®
 Reflector: ABS
 Tube: Polypropylene (Safety Orange)
 Contact Strip: Phosphor Bronze
 Switch: Polyethylene
 Bottom Cap: Polypropylene (Black)
 Ring Hanger: ABS (Safety Orange)

Product Features

- For use in hazardous atmospheres
- Division 1 UL & CUL approved
- Lower cost of maintenance
- Spare bulb compartment
- Crush Resistant Case
- Switch Guard
- Ring Hanger
- 250,000 cycle positive locking switch
- Anti-roll Tube
- Oversized, faceted reflector for more light
- Unbreakable Lens

Unit Dimensions

Length: 10.2 in. (25.1 cm)
 Width: 2.3 in. (5.8 cm) at head
 Height: N/A

Safety Approvals

UL/CUL: Class I, Div 1, Group C & D
 Class II, Div 1, Group G
 Class III
 Operating Temp T3C
CSA: Class I, Group C & D
 Class II, Group G
 Operating Temp T3C
ASTM & MSHA Approved



WorkSafe Model # 2124

Accessories

| | |
|-------|--------------------------|
| 23853 | 6 ½" Red Snap In Wand |
| 23860 | 6 ½" Yellow Snap In Wand |

Description