

Unit Information

Model #. 500304 Alkaline version
500301 w/ Ni-Cad Battery Pack

Unit Dimensions

Length: 2.5 in. (6.4 cm)
Width: 3.0 in. (7.6 cm)
Height: 7.0 in. (17.8 cm)

Specifications

Power Source: Ni-Cad Battery Pack #500200-N or
Four Alkaline C-Cell Batteries

Type	Volts	Amps	Watts
H-13	4.8	.85	4.0

Bulb/Lamp Life: 50 Hours

Light Output: 45,000 Beam Candlepower w/
Ni. Cad #500200-N, or 60,000 Beam CP w/ Alkaline
Batteries

Weight (With Nicad battery): 1.0 lbs. (2.2 kg)

Components

Lens Ring: Flame-Retardant Santoprene

Lens: Polycarbonate

Bottom Cap: Super Tough Nylon

Switch: Super Tough Nylon

Tube: Super Tough Nylon

Reflector: Ultem 1000

Contact: Foam Mesh Pad (for alkaline
batteries)

Safety Approvals

UL: Class I Division 1, Group D
Operating Temp T3
ATEX II 2 G EEX ib e IIB T3



Model # 500304 (Alkaline Version)

Product Features

- UL, CUL, & CSA Division 2 safety approved
- Glow labels (use ball point pen for name)
- Survives 30 ft drop test
- Pushbutton switch
- Waterproof
- 2 hour charge time
- Light weight (1 pound)
- 45,000 Candlepower and 2 hour burn time w/ Ni-Cad #500200-N (4.8V)
- 60,000 Candlepower and 5 hour burn time w/ Alkaline Batteries (6.0V)
- Spare bulb compartments (2)
- Halogen bulb (Do not touch glass, shortens bulb life)
- Imprinting available, pad print only

Part #'s

500301

500304

Description

Orange w/ Ni-Cad Battery
Pack

Orange w/ Four Alkaline
C-Cell Batteries