

LIGHTS

2400

StealthLite™ Zone 1

Save page as PDF



StealthLite™ 2400 Zone 1 Flashlight

Same features as the StealthLite™ 2400 with static-dissipation materials body. StealthLite 2400Z1 is ATEX certified safe for use in hazardous Zone 1 (Category 2) locations, and is perfect for professionals who work in areas with high risk of explosion such as chemical, pharmaceutical, power, oil and gas, and fire rescue.



Yellow



Gray

StealthLite™ 2400 Zone 1 Flashlight Specifications

Length	Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
16.5 cm (6.49")	Xenon	25.0	5,800

Batteries	Battery Burn Time	Battery Pack Charging Time
4 AA Alkaline (Not included)	4 hrs.	N/A

Watts	Voltage	Weight w/Batteries	Weight w/o Batteries
3.2	6	0.2 kg (7.1 oz.)	0.1 kg (3.5 oz.)

Approvals

CE Ex - II 2 G EEx e ib IIC T4
Certificate: DEMKO 01ATEX131037

Materials

Body	Lens	Shroud	Switch Type
Anti-static ABS	Polycarbonate Resin	K-resin	One-handed safety switch operation

Clip	Contact, Spring & Retainer	O-Ring	Night Vision Film
N/A	Stainless Steel and Phosphore Bronze	Ethylene Propylene	N/A

Configurations

Cat. #	Description
2400Z1	StealthLite™ 2400Z1

StealthLite™ 2400 Zone 1 Flashlight Accessories

Cat. #	Description
2404Z1	StealthLite 2400 Zone 1 Lamp Module
700	Helmet Light Holder
750	Helmet Light Holder
760	Helmet Light Holder
770	Universal Helmet Light Holder

© 2009 Peli™ Products, S.L. C/Casp 33-B, Pral. · 08010 Barcelona (Spain) · Tel: +34 93 467 4999 · Fax: +34 93 487 7393

Registered in Registro Mercantil de Barcelona, Tomo 29.581, Hoja B-155906 CIF: ES B61233201

www.peli.com