



Save page as PDF



MityLite™ 2340 Flashlight



The 2340 is a compact, convenient personal light, but is also a powerful professional duty light. A pre-focused Xenon lamp module produces a powerful, bright white, modified spot beam. The body is made of unbreakable Xenoy that resists chemicals and water. The MityLite 2340 has a push button tail for easy on/off or intermittent light. It is powered by 2 AA alkaline cells and safety approved for hazardous conditions. A must-have for every toolbox. Certified to ATEX Zone 2 (Category 3).



Black



Yellow

MityLite™ 2340 Flashlight Specifications

Length	Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
15.9 cm (6.25")	Xenon	8.0	1,200

Batteries	Battery Burn Time	Battery Pack Charging Time
2 AA Alkaline (Included in select packaging)	4 hrs.	N/A

Watts	Voltage	Weight w/Batteries	Weight w/o Batteries
1.8	3	0.1 kg (3.5 oz.)	0.05 kg (1.86 oz.)

Materials

Body	Lens	Shroud	Switch Type
Xenoy Polymer Resin	Polycarbonate Resin	Polypropylene	Push button On/Off tail switch

Clip	Contact, Spring & Retainer	O-Ring	Night Vision Film
N/A	Stainless Steel	Ethylene Propylene or Neoprene	N/A

Configurations

Cat. #	Description
2340	MityLite™ 2340

Approvals

- Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.

- Class I, Div. 2; Gp. ABCD, T3A.

- 10C-637-0

- Ex ib e IIC T4 IP67 IEC Ex TSA 06.0021X

- Class I, Div. 1; Gps.C,D T3, Conforms to STD UL783

MityLite™ 2340 Flashlight Accessories

Cat. #	Description
2304	MityLite™ 2340 Lamp Module
750	Helmet Light Holder
760	Helmet Light Holder
770	Universal Helmet Light Holder