

LIGHTS

2460

StealthLite Rechargeable Recoil LED Zone 1

Save page as PDF



StealthLite™ Rechargeable 2460 Recoil LED™ Zone 1 Flashlight

The rechargeable version of the StealthLite 2410 Recoil LED. The StealthLite Rechargeable 2460 Recoil LED uses a long-life NiMH battery pack for extended burn time. It comes with a charger base unit that can be installed at home or work using the 220 V transformer, or in a vehicle through direct wiring or 12 V plug-in. Certified to ATEX Zone 1 (Category 2).



Yellow



Gray



StealthLite™ Rechargeable 2460 Recoil LED™ Zone 1 Flashlight Specifications

Length	Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
17.8 cm (7")	Recoil LED	40.0	3,800
Batteries	Battery Burn Time	Battery Pack Charging Time	
4 AA NiMH (Included)	32 hrs.	NiMH Battery Pack 2-3 hrs.	
Watts	Voltage	Weight w/Batteries	Weight w/o Batteries
1	4.8	0.22 kg (7.8 oz.)	0.12 kg (4.4 oz.)

Materials

Body	Lens	Shroud	Switch Type
Anti-static ABS	Polycarbonate Resin	ABS	One-handed safety switch operation
Clip	Contact, Spring & Retainer	O-Ring	Night Vision Film
N/A	Stainless Steel and Phosphore Bronze	Ethylene Propylene	N/A

Configurations

Cat. #	Description
2460Z1	

Accessories

No accessories are currently available for this product

Approvals

CE Ex - II 2 G Ex ib IIC T4
Certificate: Epsilon 07ATEX2168X

